

MCCOY NINE DEPARTURE

SL-571 (FAA)

ORLANDO INTL (MCO)
ORLANDO, FLORIDA

ATIS DEP
120.525
CLNC DEL
134.7 341.7
GND CON
121.8 275.8
ORLANDO INTL TOWER
118.45 (Rwys 17L-35R, 17R-35L) 253.5
124.3 (Rwys 18L-36R, 18R-36L) 253.5

SAVANNAH
115.95 SAV
Chan 106 (Y)
N32°08.78'-W81°11.95'
L-24, H-9-12

TAKEOFF MINIMUMS:

Rwys 18L, 18R, 17L, 17R, 35L, 36L, 36R Standard.

Note: Rwy 35R, 300-1 or Standard with minimum climb of 340 feet per NM to 400.

Note: Rwys 35L, 35R, 36L, 36R require an ATC climb gradient of 600 feet per NM to 2800 Feet. If unable to accept this ATC climb gradient, advise ATC on initial contact.

TAKEOFF OBSTACLE NOTES:

NOTE: Rwy 17L, Numerous trees from 1080 feet to 1725 feet from DER, from 600 feet to 740 feet left of centerline, from 44 feet AGL/134 feet MSL to 53 feet AGL/143 feet MSL.

NOTE: Rwy 35R, Tree 2225 feet from DER, 730 feet right of centerline, 94 feet AGL/184 feet MSL.

VIYAP
N31°15.14'
W81°26.14'

CRAIG
114.5 CRG
Chan 92
N30°20.33'-W81°30.60'

ORMOND BEACH
112.6 OMN
Chan 73

GUANO
N29°05.98'
W81°23.32'

ORLANDO
112.2 ORL
Chan 59
N28°32.56'-W81°20.10'

NOTE: Turbojets only.
NOTE: DME required.
NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

MCCOY NINE DEPARTURE

SE-3, 03 JUL 2008 to 31 JUL 2008

SE-3, 03 JUL 2008 to 31 JUL 2008