

RIVER VISUAL RWY 25L

AL-322 (FAA)

PHOENIX SKY HARBOR INTL (PHX)
PHOENIX, ARIZONA

PHOENIX APP CON
126.8 256.9
128.65 353.8
PHOENIX TOWER
120.9 254.3 Rwy 7L-25R, 7R-25L
118.7 385.4 Rwy 8-26
GND CON
119.75 N
132.55 S
CLNC DEL
118.1 269.2
ATIS 127.575

ARIZONA BILTMORE



2704
CAMELBACK MOUNTAIN

Vertical Guidance Navaid
and Angle
PAPI Rwy 25L-3.00°

PHOENIX
115.6 PXR
Chan 103

RED MOUNTAIN FREEWAY

8 7L 7R
25L 25R 26

MARICOPA
FREEWAY

1548 TEMPE BUTTE
POWER PLANT

PIMA FREEWAY

3100 Recommended Minimum

Base leg east of the Power Plant.

Complete base leg turn at or above 4000 feet.

For noise abatement intercept final east of Power Plant at or above 3100.

Routes depicted are reference only providing turns east of Power Plant.

Complete base leg turn at or above 4000 feet.

Base leg east of the Power Plant.

RADAR REQUIRED

Weather Minimums: 4500 feet ceiling and 8 mile visibility.

SOUTH MOUNTAIN
3047

4000 Recommended

SW-4, 03 JUL 2008 to 31 JUL 2008

SW-4, 03 JUL 2008 to 31 JUL 2008

1 NM	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
------	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----

RIVER VISUAL RWY 25L

When visual approaches to Runway 25L are in progress, clearances will be given utilizing in part the following phraseology:

"(IDENT) CLEARED FOR A RIVER VISUAL RUNWAY 25L APPROACH"

RIVER VISUAL RWY 25L