

8002 TUR 13 01 8002Z TUR 03 12-05

TAKE-OFF MINIMUMS

Rwys 17C/R, 18L/R: Standard with minimum ATC climb of 500' per NM to 5000.
Rwys 35C/L, 36L/R: Standard with minimum ATC climb of 500' per NM to 5500.
Rwys 13L/R, 17L, 31L/R, 35R: NA - ATC request.

NOTE: 1. DME/DME/IRU or GPS Required.
2. RNAV 1.

NOTE: For Turbo Jets only.

NOTE: Radar Required.

NOTE: Chart not to scale

TAKE-OFF MINIMUMS

Rwys 17C/R, 18L/R: Standard with minimum ATC climb of 500' per NM to 5000.
Rwys 35C/L, 36L/R: Standard with minimum ATC climb of 500' per NM to 5500.
Rwys 13L/R, 17L, 31L/R, 35R: NA - ATC request.




NOTE: 1. DME/DME/IRU or GPS Required.
2. RNAV 1.

NOTE: For Turbo Jets only.

NOTE: Radar Required.

NOTE: Chart not to scale

NOTE:
Rwys 35L/C, 36L/R: Do not exceed 230K until KMART WP.
Rwys 17C/R, 18L/R: Do not exceed 230K until LARRN WP.




ATIS 135.925
CLNC DEL 128.25
GND CON
121.65 121.8 (EAST)
121.85 (WEST)
DFW TOWER
126.55 127.5 (EAST)
124.15 134.9 (WEST)
REGIONAL DEP CON
126.47 363.15

KMART
5500 230K

MARSN
257° (4)
260° (4)
GVINE

323°
325°
336°
338°
1110
1080

N



354°
354°
174°
174°
1100
1080

MILLSAP
MQP

PODDE

1080

ABILENE
ABI

TANNO

LARRN

4000

4000

5000

256° (96)

264° (13)

251° (4)

268° (24)

268° (6)

183°
182°

(NARRATIVE ON FOLLOWING PAGE)

SC-2, 03 JUL 2008 to 31 JUL 2008

PODDE THREE DEPARTURE (RNAV)

(PODDE3.PODDE) 08045

SL-6039 (FAA)

DALLAS-FORT WORTH INTL (DFW)
DALLAS-FORT WORTH, TEXAS

DALLAS-FORT WORTH, TEXAS
DALLAS-FORT WORTH INTL (DFW)